NEDONG REHABILITATION DEVICE ACCESSORIES SERIES

Honeycomb Structure
Shock Absorption and More Comfortable

TPE Material
Eco-friendly, Odourless and Anti-cracking

Anti-ageing & Durable
No Change in Hardness Within 5 Years

NEDONG WHEELCHAIR TIRES
【FEATURES】

Material is environmentally friendly and odourless

Shock absorption leads to better riding experience

Grip design promises the riding safety

Portable,durable and maintenance-free

Model	6x1.4 Wheel Set		
Diameter	143mm	Width	35mm
Bearing Height	46mm		
Bearings	608z		

Model	6x1.8 Wheel Set		
Diameter	153.6mm	Width	46mm
Bearing Height	54mm	Bearings	6001..608z
Pin Size	17-5°5 / 17-6°6 / 19-5°5 / 19-6°6		

Model	7x1.8 Wheel Set		
Diameter	180mm	Width	46mm
Bearing Height	54mm	Bearings	6001..608z
Pin Size	17-5°5 / 17-6°6 / 19-5°5 / 19-6°6		

Model	8x1.3 Wheel Set		
Diameter	186.5mm	Width	33mm
Bearing Height	45mm	Bearings	608z
Pin Size	/		

Model	8x1.8		8x2.0
Width	46mm		51mm
Diameter	188mm	Bearing Height	55mm
Bearings	6000, 608z		



Model	8x2.4 Wheel Set		
Diameter	194mm	Width	61mm
Bearing Height	58mm	Bearings	6001..608z
Pin Size	17-5°5 / 17-6°6 / 19-5°5 / 19-6°6		

Model	10x1.5 Wheel Set		
Diameter	239mm	Width	38mm
Bearing Height	40mm	Bearings	6001
Pin Size	/		

Model	10x2.125 Wheel Set		
Diameter	245.5mm	Width	55mm
Bearing Height	For 10inch aluminium alloy rim		
Pin Size	17-6°6		

Model	12x2.125 Wheel Set		
Diameter	287mm	Width	55mm
Bearing Height	For 10inch aluminium alloy rim		
Pin Size	17-6°6		

Model	12x2.5 Wheel Set		
Diameter	311mm	Width	63mm
Axle Sleeve	53mm		
Pin Size	17-5°5 / 17-6°6		

Model	12x1.5 Wheel Set		
Diameter	260mm	Width	38mm
Pin Size	/		
Axle Sleeve	Axle Type(1004E), Bearing Type(6001)		

Model	12x2.0 Wheel Set		
Diameter	288mm	Width	48mm
Bearing Height	54mm	Bearings	6001
Pin Size	/		

Model	20x1.0 Tire		
Diameter	483mm	Width	27mm
Suitable Rim Groove Width	18.5mm		
Suitable Rim Diameter	460mm		

Model	22x1.1 Tire		
Diameter	518mm	Width	27mm
Suitable Rim Groove Width	18.5mm		
Suitable Rim Diameter	520mm		

Model	24x1.1 Tire		
Diameter	573mm	Width	27mm
Suitable Rim Groove Width	18.5mm		
Suitable Rim Diameter	550mm		

Model	Light Weight Shock Absorbing Rubber Feet		
Weight	57g±5%	Height	76mm
Material	TPE	Hardness	67A
Adaptive Pipe Diameter	19mm		